



# Model ST-375

## Rotary Scale Clamp Meters



### ST-375 Rotary Scale Clamp Meter


- Rotary scale which presents only one scale in windows at one time to avoid any possible reading errors.
- Pointer lock function freezes the reading in dimly lit or hard to reach places.
- $\Omega$  range ideal for checking the continuity or relays, transformers and motor coils.

### Specifications

|                           |  |
|---------------------------|--|
| ACA                       | 6 / 15 / 60 / 150 / 300A<br>$\pm 3\%$ of F.S.(50/60Hz)           |
| ACV                       | 300 / 600V<br>$\pm 3\%$ of F.S.                                  |
| DCV                       | 75V<br>$\pm 3\%$ of F.S.   |
| $\Omega$                  | 2k $\Omega$<br>$\pm 3\%$ of Scale length                         |
| Frequency response        | 50 / 60Hz for ACA 6A<br>50-400Hz for ACA<br>15 / 60 / 150 / 300A |
| Dimensions                | 230(L) $\times$ 72(W) $\times$ 37(D)mm                           |
| Conductor size            | 38mm Max.  |
| Weight (battery Included) | Approx. 420g   |
| Safety standard           | EN 61010-1 CAT II 600V<br>EN 61010-2-32                          |

### Accessories

- Instruction manual
- Test leads
- Soft pouch



AL-24-1



CAC-600