



Model ST-368TR

Analog Multimeter



CE

- Taut band movement.
- Easy to read 3-color scale...for mistake proof reading.
- Mirror scale...makes reading pointer easy.
- Safety fused...on all ranges.
- Diode protected meter...prevents damage due to overload.
- Safety features...safety fused, safety "OFF" position.
- hFE and dB measurement.
- LCD check function.
- Battery test function.
- Continuity test function.
- With stand...makes reading and measuring easy.

Specifications

| | |
|-----------------|-------------------------------------------------------|
| DC volts | 0-0.1 / 0.5 / 2.5 / 10 / 50 / 250 / 1000V(20kΩ/V) |
| AC volts | 0-10 / 50 / 250 / 1000V |
| DC mA | 50uA / 2.5 / 25 / 250mA |
| OHMS | 2k / 20k / 200k / 2M / 20MΩ (20 Mid-Scale) |
| Accuracy | ±3% F.S. DC. ± 4% F.S. AC. |
| Sensitivity | 20kΩ/V DC. 9kΩ/V AC. |
| dB | -10dB ~ +22dB |
| hFE | 0-1000 |
| LED check | √ |
| Battery check | GOOD or BAD |
| ICEO | 1.5mA, 15mA, 150mA |
| LV | LV 3V~0V |
| Dimensions | 100(L) × 150(W) × 41(D)mm |
| Weight | Approx. 340g (battery included) |
| Power source | 1.5V (AA) × 2, 9V(6F22) × 1 |
| Safety standard | EN 61010-1 CAT II 1000V EN 61010-2-030, EN 61326-1 |