



Model VOT-51

Voltage/Continuity Testers



Features

- Voltage test: 12V to 690V AC/DC (7 LEDs) with indication by buzzer.
- Voltage range: 12V, 24V, 50V, 127V, 230V, 400V, 690V.
- Polarity test: LED +/-
- Audible continuity test
- Self-test button to ensure proper function of the device prior to testing.
- Waterproof design, protection class: IP54
- Phase / Neutral identification
- Integrated storage clips for test probe.
- Rubberized injection molding..

Specifications

Voltage test	12V to 690V AC/DC
Voltage range	AC : 12V,24V,50V,127V,230V,400V,690V DC : 12V,24V,50V,127V,230V,400V,690V
Flashlight	✓
Working frequency	40 to 400 Hz
Voltage protection	1000V DC / 700V AC
Continuity range	6k Ω
Resistance range	6k Ω ,60k Ω ,300k Ω
Operating temperature	0 - 40°C
Operating humidity	80% R.H.
Probe distance	19mm apart
Dimensions	195(L) x 56(W) x 35(D)mm
Weight (battery included)	Approx. 214g
Power source	9V(6F22) x 1
Safety standard	EN 61010-1 CAT III 600V EN 61243-3 EN 61326-1

Accessories

- Instruction manual
- Soft pouch
- Battery