



## **Hoyt AC Voltage Proving Units**

HLV-1 .....	1
HLV-2 .....	2
HLV-3 .....	3

## HLV-1 AC Voltage Proving Unit

### Features

- Designed to proof.  
AC voltage detectors  
AC voltage testers
- Compact, handheld, and easy to carry and use.
- Battery operated.
- LED indicates when power is "ON".
- Normal 4mm test leads.

### Specifications

Output voltage	H terminal: AC 400V ( $\pm 20\%$ ) L terminal: AC 100V ( $\pm 20\%$ )
----------------	--

Frequency	50-60Hz
-----------	---------

Power on indicator	✓
--------------------	---

### General

Operating temperature	0°C ~ 40°C
Dimensions	124(L) × 69(W) × 42(D)mm
Weight	Approx. 305g (battery included)
Power source	9V(6F22) × 1
Safety standard	EN 61010-1 EN 61326-1

### Accessories

- Battery
- Test leads (20cm) × 2 (Optional)



## HLV-2 AC Voltage Proving Unit

### Features

- Designed to proof.
  - AC voltage detectors
  - AC voltage testers
- Compact, handheld, and easy to carry and use.
- Battery operated.
- LED indicates when power is "ON".
- Normal 4mm test leads..



### Specifications

Output voltage	H terminal: AC 400V ( $\pm 20\%$ ) L terminal: AC 100V ( $\pm 20\%$ )
Frequency	50-60Hz
Power on indicator	✓

### General

Operating temperature	0°C ~ 40°C
Dimensions	128(L) x 72(W) x 45(D)mm
Weight	Approx. 315g (battery included)
Power source	9V(6F22) × 1
Safety standard	EN 61010-1 EN 61326-1

### Accessories

- Battery
- Test leads (20cm) × 2 (Optional)

CE

## HLV-3 AC Voltage Proving Unit

### Features

- Designed to proof.
  - AC voltage detectors
  - AC voltage testers
- Compact, handheld, and easy to carry and use.
- Battery operated.
- LED indicates when power is "ON".
- Normal 4mm test leads.



### Specifications

Output voltage	H terminal: AC 415V ( $\pm 20\%$ ) L terminal: AC 230V ( $\pm 20\%$ )
Frequency	50-60Hz
Power on indicator	✓

### General

Operating temperature	0°C ~ 40°C
Dimensions	128(L) x 72(W) x 45(D)mm
Weight	Approx. 315g (battery included)
Power source	9V(6F22) × 1
Safety standard	EN 61010-1 EN 61326-1

### Accessories

- Battery
- Test leads (20cm) × 2 (Optional)

