



Model ST-3502

Analog + Digital Multimeter



Specifications

DC Voltage (Input impedance: 10MΩ)

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200mV	240mV	100µV			DC500V
2V	2.4V	1mV			AC350V
20V	24V	10mV	±(1%rdg+1dgt)	±3%F.S.	DC1200V
200V	240V	100mV			AC800V
600V	600V	1V			

AC Voltage (Input impedance: 10MΩ)

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200mV	240mV	100µV			DC500V
2V	2.4V	1mV			AC350V
20V	24V	10mV	±(1%rdg+5dgt)	±3%F.S.	DC1200V
200V	240V	100mV			AC800V
600V	600V	1V	±(1.5%rdg+5dgt)		

DC Current

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200uA	240uA	100nA			
2mA	2.4mA	1µA			
20mA	24mA	10µA	±(1%rdg+5dgt)	±3%F.S.	800mA
200mA	240mA	100µA			
10A	10A	10mA	±(2%rdg+3dgt)		10A

AC Current

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200uA	240uA	100nA			
2mA	2.4mA	1µA			
20mA	24mA	10µA	±(1%rdg+5dgt)	±3%F.S.	800mA
200mA	240mA	100µA			
10A	10A	10mA	±(2%rdg+3dgt)		10A

- 3½ digit, high contrast LCD, with a maximum display of 1999
- Automatic polarity indication, zero adjustment
- Low battery (BAT) indication
- Over range indication: highest digit of (1) or (-1)
- EN 61010-1 CAT III 600V, EN 61326-1

ANALOG DISPLAY

- Large 90° wide and 84mm long mirror scale. (adapted to digital, analogue maximum indication 2400)
- Shock and vibration resistant TAUT BAND movement
- Pointer can be selected to either left-hand zero (normal mode) or center zero (galvo-mode)
- In galvo-mode pointer deflects right to indicate positive polarity and left to indicate negative polarity
- Automatic center zero and ohm zero
- Dimensions: 175(L) × 109(W) × 44(D)mm

Resistance

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200Ω	5kΩ	100mΩ			±4%arc
2kΩ	50kΩ	1mΩ			-10Ω
20kΩ	500kΩ	10Ω			±(1%rdg+5dgt)
200kΩ	5MΩ	100Ω			50V DC
2000kΩ	50MΩ	1kΩ			±4%arc
20MΩ	500MΩ	10kΩ	±(1.5%rdg+5dgt)		

Capacitance

Range	Analog Maximum	Resolution Digital	Accuracy		Test Voltage
			Digital	Analog	
2000pF	2400pF	1pF			
20nF	24nF	10pF			
200nF	240nF	100pF	±(3%rdg+10dgt)	±5%F.S.	50mV
2uF	2.4nF	1nF			400Hz
20uF	24uF	10nF			

Instant Continuity

Range	Analogue Maximum	Resolution Digital	Continuity Indication		Open Voltage
			Digital	Analog	
200Ω	5kΩ	100mΩ	Built Buzzer sounds when Resistance is less than 40Ω		3.2V MAX

Frequency

Range	Analogue Maximum	Resolution Digital	Accuracy		Test Voltage
			Digital	Analogue	
2000Hz	2400Hz	1Hz	±(2%rdg+3dgt)	±3%F.S.	350Vrms

hFE Test

Base DC Current	Vce	hFE
10µA	2.8 ± 0.4V	1000

Diode Test

Test Current	Test Voltage
3.0 ± 0.6mA	3.2V Max.

Hoyt Electrical Instrument Works, Inc.

23 Meter Street
Penacook, NH 03303

Phone: (800) 258-3652

Fax: (603) 753-9592

Email: sales@hoymeter.com

www.hoymeter.com

Page 1 (1)