
weasuring the None


DLA-30-ACV-300 AC Voltmeter

Digital Panel Meter









Range: 0 - 285VAC

Features

Digital AC Voltmeter with 3.5 Digit red high intensity LED Display.

Range: 0-285VAC.

Completely Isolated. Field Adjustable.

Marine – Ideal for ship to shore panels.

Generators – Ideal for generator panels.

Specifications

Display

0.56" Red High Intensity digits with terminal blocks (isolated design).

Polarity: automatic, "-" displayed.

Overrange: three lower order digits blank.
for inputs >1999 & <- 1999.

Performance:

0-285 AC Voltmeter. 12-24VDC AUX Power.

Accuracy: $(\pm 0.05\% \text{ FS} + 1 \text{ count})$. Sample Rate: 3 readings per second.

Field Adjustable: single turn potentiometer for calibration.

Warmup: 10 minutes typical. Temperature Coeff.: ±100PPM per °C.

Power Supply:

Supply Voltage: 12-24VDC.

Environment:

Operating Range: -10 to 50 °C Storage Range: -40 to 75 °C.

Connection:

Terminal Block Connections. Spade terminals.

NOTE: manufactured part numbers have changed. DMC-30-ACV-300 has been replaced by DLA-30-ACV-300.

Hoyt Electrical Instrument Works, Inc.

23 Meter Street Penacook, NH 03303 Phone: (800) 258-3652

Fax: (603) 753-9592 Email: sales@hoytmeter.com www.hoytmeter.com

Page 1 (1)