
weasuring the World


DLA-30-ACF-60 AC Frequency Meter

Digital Panel Meter









Input: 40 - 90 HZ 120 / 240VAC

Features

Digital AC Frequency Meter with 3.5 Digit red high intensity LED Display. Frequency, 50 or 60 Hertz.

Completely Isolated. Field Adjustable.

Marine – Ideal for ship to shore panels.

Generators – Ideal for generator panels.

Specifications

Display

0.56" Red High Intensity digits with terminal blocks (isolated design).

Polarity: automatic, "-" displayed.

Overrange: three lower order digits blank for inputs >1999 & <- 1999.

Performance:

24VDC AUX Power.

Frequency, 50 or 60 Hertz.

Accuracy: $(\pm 0.05\% \text{ FS} + 1 \text{ count})$. Sample Rate: 3 readings per second.

Field Adjustable: single turn potentiometer for calibration.

Warmup: 10 minutes typical.
Temperature Coeff.: ±100PPM per °C.

Power Supply:

Supply Voltage: 12-24VDC.

Environment:

Operating Range: -10 to 50 °C Storage Range: -40 to 75 °C.

Connection:

Terminal Block Connections. Spade terminals.

NOTE: manufactured part numbers have changed. DMC-30-ACF-60 has been replaced by DLA-30-ACF-60.

Hoyt Electrical Instrument Works, Inc.

23 Meter Street Penacook, NH 03303 Phone: (800) 258-3652

Fax: (603) 753-9592

Email: sales@hoytmeter.com

www.hoytmeter.com

Page 1 (1)